



## TURMOWOODOIL FD 15



Date of issue: 07.05.2019

**TURMOWOODOIL FD 15** is a fully synthetic high temperature chain oil. It is particularly suitable for dusty environments.

### Special properties

- Excellent adhesion
- High temperature stability
- Low volatility
- Low dust binding
- Excellent corrosion and wear protection
- Very high ageing stability
- Stable to cold and hot water as well as water steam
- Suitable for nonferrous metals
- Silicone-free

Product Characteristics	Value	Dimension	Norm / Standard
Colour	orange, clear		
Density at 20°C	0,98	g/cm <sup>3</sup>	DIN 51757
Operating temperature range	-20 to 280	°C	
Oil type	Ester		
Kinematic viscosity at 40°C	64,4	mm <sup>2</sup> /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	8,7	mm <sup>2</sup> /s	DIN EN ISO 3104
Viscosity index (VI)	108		DIN ISO 2909
Pour point	< -20	°C	DIN ISO 3016
Flash point	> 270	°C	DIN EN ISO 2592

### Application

Chains at high ambient temperatures, in conveyor chains in the cardboard industry, the wood industry, in driers, hot-water and steam plants as well as film stretching machines.

**TURMOWOODOIL FD 15** may be applied by drip feed oiler and automatically by pump, spray and dosing systems which are suitable for this viscosity.

### Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)  
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>