



TURMOCUT VG 22



Date of issue: 15.12.2016

TURMOCUT VG 22 is a fully synthetic cutting oil.

Special properties

- High metal affinity
- Very good surface wetting abilities
- Very good creeping ability
- Excellent lubricating properties
- Good corrosion protection
- Good pumpability

Product Characteristics	Value	Dimension	Norm / Standard
Colour	light yellow		
Density at 20°C	0,89	g/cm ³	DIN 51757
Operating temperature range	-30 to 150	°C	
Oil type	synthetic hydrocarbons		
Kinematic viscosity at 40°C	20,5	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	3,9	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	85		DIN ISO 2909
Pour point	-35	°C	DIN ISO 3016
Flash point	> 140	°C	DIN EN ISO 2592

Application

TURMOCUT VG 22 is used for the lubrication of longitudinal cutters and the Disc-Cut Systems in the paper and cardboard industry.

Packaging units

5 l canister, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>