



COMPGUARD FG 32



Date of issue: 09.02.2017

COMPGUARD FG 32 is an universal compressor oil for high and low temperatures and extreme operating conditions. Compared with conventional products on mineral base, this oil is distinguished by its wide temperature range and high resistance of oxidation.

COMPGUARD FG 32 is InS/H1 approved as lubricant for which an incidental contact with food technically cannot be avoided.

Special properties

- High load carrying capacity
- Low coefficient of friction
- Neutral towards elastomers and plastics
- No corrosion of nonferrous metals up to 100°C

Product Characteristics	Value	Dimension	Norm / Standard
Colour	clear, transparent		
Density at 20°C	0,83	g/cm ³	DIN 51757
Operating temperature range	to 160	°C	
Oil type	synthetic hydrocarbons		
Kinematic viscosity at 40°C	32	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	5,9	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	143		DIN ISO 2909
Pour point	-55	°C	DIN ISO 3016
Flash point	> 220	°C	DIN EN ISO 2592

Application

COMPGUARD FG 32 compressor oil is for universal application in rotary screw compressors, reciprocating and piston compressors, as well as for hydraulic and chain lubrication.

When being used in compressors, the oil changing intervals are up to 4000 operating hours.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



1795173



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>