



COMPGUARD GPX 32



Date of issue: 26.08.2019

COMPGUARD GPX 32 is a fully synthetic high performance compressor oil with excellent lubricating properties.

Special properties

- Excellent corrosion and wear protection
- High load carrying capacity
- Stable to temperature
- Low generation of residue
- High oxidation resistance
- High ageing stability for extended oil change intervals

Product Characteristics	Value	Dimension	Norm / Standard
Colour	colourless, transparent		
Density at 20°C	0,84	g/cm ³	DIN 51757
Operating temperature range	-20 to 120	°C	
Oil type	Mixture of synthetical oils		
Kinematic viscosity at 40°C	32	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	6,1	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	141		DIN ISO 2909
Pour point	< -40	°C	DIN ISO 3016
Flash point	> 220	°C	DIN EN ISO 2592

Application

Rotary vane pumps, reciprocating compressors and crank cases.

Packaging units

5 l canister, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>