



COMPGUARD HT 46



Date of issue: 09.04.2018

COMPGUARD HT 46 is a fully synthetic compressor oil with excellent lubricating properties.

Special properties

- Exceptional temperature stability
- High oxidation resistance
- Low volatility
- High ageing stability for extended oil change intervals
- Easy cleaning of the machine parts because there is no hard incrustation
- Reduces energy consumption

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellowish		
Density at 20°C	0,96	g/cm ³	DIN 51757
Operating temperature range	to 220	°C	
Oil type	Ester		
Kinematic viscosity at 40°C	46	mm ² /s	DIN EN ISO 3104
Pour point	< -25	°C	DIN ISO 3016
Flash point	> 240	°C	DIN EN ISO 2592

Application

COMPGUARD HT 46 is used in all types of rotary screw compressors, rotary vane compressors and reciprocating compressors.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>