



ELASTOLUB SLO



Date of issue: 17.11.2016

ELASTOLUB SLO is an assembly lubricant based on silicone oil.

Special properties

- Neutral towards elastomers except silicon rubber
- Wide temperature range
- Low vapour pressure
- Odourless

Product Characteristics	Value	Dimension	Norm / Standard
Colour	clear, transparent		
Density at 20°C	0,97	g/cm ³	DIN 51757
Operating temperature range	-55 to 210	°C	
Oil type	silicone oil		
Kinematic viscosity at 25°C	100000	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 40°C	75000	mm ² /s	DIN EN ISO 3104
Pour point	-50	°C	DIN ISO 3016

Application

ELASTOLUB SLO is used as highly viscous assembly lubricant as well as sealing and release agent particularly for material combinations of plastic / plastic.

ELASTOLUB SLO is suitable for applications under vacuum conditions even in high pressure range.

Packaging units

100 g tube, 0,5 kg can, 1 kg can, 5 kg bucket, 25 kg hobbock

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>