



GRIZZLYGREASE No. 1 NLGI 1

K P 1 N -30



Date of issue: 14.09.2020

GRIZZLYGREASE No. 1 NLGI 1 is an adhesive lubricant based on a high-viscosity mineral oil and a lithium/calcium complex soap with high pressure additives. These additives are combined with the soap structure so that an optimum adhesiveness to the metal surface is possible.

Special properties

- Remarkable adhesive properties
- High load carrying capacity
- Excellent corrosion and wear protection
- High work resistance
- High resistance to water
- Resistant to radioactive radiation

Product Characteristics	Value	Dimension	Norm / Standard
Colour	dark brown		
Density at 20°C	0,96	g/cm ³	DIN 51757
Operating temperature range	-30 to 150	°C	
Thickener	Li / Ca special soap		
Base oil	Mineral oil		
Kin. viscosity of the base oil at 40°C	980	mm ² /s	DIN EN ISO 3104
Kin. viscosity of the base oil at 100°C	55	mm ² /s	DIN EN ISO 3104
Worked penetration	310 – 340	mm/10	DIN ISO 2137
Consistency class (NLGI)	1		DIN 51818
Dropping point	> 220	°C	DIN ISO 2176
Resistance to water	0 – 90		DIN 51807
Corrosion protection (SKF-Emcor)	0 / 0		DIN 51802
Speed factor of grease (n x dm)	100 000	mm/min	
Four-ball test O.K. load / welded load	5000 / 5500	N	DIN 51350
Resistance to radioactive radiation	1,2 x 10 ⁶	Gy (=10 ² rd)	

Application

Due to the high temperature properties **GRIZZLY GREASE No. 1 NLGI 1** can be used for a wide range of applications, where high temperatures and high loads exist.

GRIZZLY GREASE No. 1 NLGI 1 is among other applications recommended for slow running ball bearings and roller bearings, for slide bearings/bushes, open gears and couplings.

Packaging units

20 x 400 g cartridges, 6 x 1 kg cans, 5 kg bucket, 25 kg hobbock, 50 kg hobbock, 180 kg drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>