



GRIZZLYGREASE No. 2

K P 3 N -30



Date of issue: 14.09.2020

GRIZZLYGREASE No. 2 is a damping grease and an adhesive lubricant.

GRIZZLYGREASE No. 2 based on a lithium/calcium complex with high pressure additives, which are combined with the soap structure so that an optimum adhesiveness to the metal surface is possible.

Special properties

- High resistance to temperature
- Excellent high load carrying capacity
- Excellent corrosion and wear protection
- Remarkable damping properties and adhesive properties

Product Characteristics	Value	Dimension	Norm / Standard
Colour	olive green - metallic		
Density at 20°C	1,02	g/cm ³	DIN 51757
Operating temperature range	-30 to 150	°C	
Thickener	Li / Ca special soap		
Base oil	Mineral oil		
Kin. viscosity of the base oil at 40°C	800	mm ² /s	DIN EN ISO 3104
Kin. viscosity of the base oil at 100°C	40	mm ² /s	DIN EN ISO 3104
Worked penetration	220 – 250	mm/10	DIN ISO 2137
Consistency class (NLGI)	3		DIN 51818
Dropping point	> 220	°C	DIN ISO 2176
Resistance to water	0 – 90		DIN 51807
Corrosion protection (SKF-Emscor)	0 / 0		DIN 51802
Speed factor of grease (n x dm)	100 000	mm/min	
Resistance to radioactive radiation	1,2 x 10 ⁶	Gy (=10 ² rd)	

Application

GRIZZLY GREASE No. 2 can be recommended for ball bearings and roller bearings as well as for slide bearings/bushes which are exposed to vibrations.

Due to the high temperature properties **GRIZZLY GREASE No. 2** can be used for a wide range of applications, where high temperatures and high loads exist.

Packaging units

6 x 1 kg can, 5 kg bucket, 25 kg hobbock, 180 kg drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>