

We have the solution...

...the future has a name



Technische Information

LUBRICANT CONSULT GMBH

Gutenbergstraße 13 · D-63477 Maintal – Germany · Telefon: +49-61 09 - 76 50-0 · Fax: +49-61 09 - 76 50-51 · Internet: www.lubcon.com

Terragloss WZ

LUBCON – Biodegradable Lubrication Dispersion

Product Feature

Terragloss WZ is a clear coloured lubricating grease with solid lubricants offering excellent protection against fretting corrosion and tribo-corrosion in relation with high qualified additives.

Terragloss WZ is resistant against extreme high-pressure loads and due to its special base oil, this product is also applicable under low temperatures. For a better application of the lubricant and to avoid dirt-adherence, it has been dispersed with a biodegradable solution.

Quality Feature

- water resistance
- good adhesiveness
- pressure stable
- with reliable corrosion protection

Technical Data

Terragloss WZ

Structure	fluid
Colour	light beige
Base oil	Ester
Thickener	Li/Ca soap, solid matters
Operating temperature	-40°C up to +130°C*
Dropping Point °C DIN ISO 2176	> 150*
Worked penetration mm/10 DIN ISO 2137	ca. 270*

(* - Values valid according to the evaporation of the solvent)

Application

For all lubricating points, where a biodegradable product is necessary due to ecological requirements without limiting the service reliability.

Original Packings:

6 x 5 ltr. cans, 20 ltr. cans, 60 l drum – not returnable.

Die Produkte unterliegen strengen Fertigungskontrollen und erfüllen die eigenen Werksspezifikationen. Eine Gewähr für die Bewährung in jedem Einzelfall kann infolge der Vielzahl der jeweils vorliegenden Faktoren jedoch nicht gegeben werden. Deshalb empfehlen wir die Durchführung von Praxisversuchen. Jegliche Haftung bleibt ausdrücklich ausgeschlossen.