



TURMOFLUID MB



Date of issue: 23.07.2018

TURMOFLUID MB is a chain oil with very good adhesiveness and optimum wear and corrosion protecting properties suitable to all operating temperature ranges.

Special properties

- High load carrying capacity
- Excellent corrosion and wear protection
- Good adhesive properties
- Wide temperature range
- High active substance content

Product Characteristics	Value	Dimension	Norm / Standard
Colour	amber coloured, transparent		
Density at 20°C	0,90	g/cm ³	DIN 51757
Operating temperature range	-15 to 150	°C	
Oil type	Mineral oil		
Kinematic viscosity at 40°C	320	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	24,8	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	99		DIN ISO 2909
Pour point	-18	°C	DIN ISO 3016
Flash point	> 270	°C	DIN EN ISO 2592

Application

TURMOFLUID MB is used for lubrication of conveyor chains in the wood and textile industry, for lifting, control and drive chains of forklift trucks, construction and machine tools, as well as for load carrying chains in roll mills.

Packaging units

12 x 400 ml spray cans, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>