



## TURMOCUT LMI 22



Date of issue: 24.08.2020

**TURMOCUT LMI 22** is a fully synthetic cutting, cleaning and preserving oil for the paper and corrugated board industry.

**TURMOCUT LMI 22** is NSF H1 registered as lubricant for which an incidental contact with food technically cannot be avoided.

### Special properties

- Very good surface wetting abilities
- Excellent lubricating properties
- Very strong dirt dissolving properties
- Exceptional penetration capacity of the felt
- Good heat dissipation

Product Characteristics	Value	Dimension	Norm / Standard
Colour	colourless, transparent		
Density at 20°C	0,95	g/cm <sup>3</sup>	DIN 51757
Operating temperature range	-5 to 220	°C	
Oil type	Ester		
Kinematic viscosity at 40°C	15	mm <sup>2</sup> /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	3,6	mm <sup>2</sup> /s	DIN EN ISO 3104
Viscosity index (VI)	125		DIN ISO 2909
Pour point	< -5	°C	DIN ISO 3016
Flash point	> 240	°C	DIN EN ISO 2592

### Application

**TURMOCUT LMI 22** is used for the lubrication of the disc-cut-systems and to clean the corrugating rolls from glue and paper dust deposits.

### Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



133126



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>