



TURMODENT H 1 plus



Date of issue: 12.11.2013

TURMODENT H 1 plus is a special oil for dental area.

Special properties

- Tasteless
- Odour of mint
- Resistant against water and disinfecting alcohol
- Excellent sealing compatibility
- Very good flow properties
- Very good corrosion protection
- High ageing stability

Product Characteristics	Value	Dimension	Norm / Standard
Colour	colourless to light yellowish		
Density at 20 °C	0,86	g/cm ³	DIN 51757
Operating temperature range	-10 to 140	°C	
Oil type	Mixture of synthetical oils		
Kinematic viscosity at 40 °C	16	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100 °C	3,9	mm ² /s	DIN EN ISO 3104

Application

TURMODENT H1 plus serves for the care and lubrication of high-speed sliding and rolling bearings in turbines and dental engines.

Corresponding to the requirements in the medical/technical area, **TURMODENT H1 plus** has an excellent flow behaviour and reaches even difficult accessible lubricating points.

Packaging units

12 x 300 ml Spray cans, 6 x 1 l bottles, 5 l canister, 20 canister, 60 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>