



TURMOFLON PTFE 14457-N



Date of issue: 04.03.2020

TURMOFLON PTFE 14457-N is a white PTFE powder which improves the wear resistance as well as the non-stick and sliding properties in thermoplastics or coating materials.

Special properties

- Chemically inert to almost industrial chemicals and solvents
- Exceptional dielectric properties
- Very high ageing stability
- Stable to temperature

Product Characteristics	Value	Dimension	Norm / Standard
Colour	white		
Density at 20°C	2,2	g/cm ³	DIN 51757
Bulk density	520	g/l	
Average particle size	450	µm	
Operating temperature range	to 260	°C	
Melting temperature	325	°C	

Application

TURMOFLON PTFE 14457-N is used as lining material as well as lubricant and release agent in various industrial sectors.

Packaging units

6 kg hobbock, 10 kg hobbock, 25 kg hobbock



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>