



TURMOFLUID 130 OM



Date of issue: 13.11.2018

TURMOFLUID 130 OM is a fully synthetic adhesive lubricating oil.

TURMOFLUID 130 OM meets the CLP requirements according DIN 51517.

Special properties

- Excellent adhesion
- Excellent corrosion protection
- High oxidation resistance
- Reduces friction and wear
- Very high load carrying capacity
- Easy cleaning of the machine parts because there is no hard incrustation

Product Characteristics	Value	Dimension	Norm / Standard
Colour	green-transparent		
Density at 20°C	0,91	g/cm ³	DIN 51757
Operating temperature range	-5 to 250	°C	
Oil type	Synthetic Hydrocarbons		
Kinematic viscosity at 40°C	1600	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	158	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	215		DIN ISO 2909
Pour point	-10	°C	DIN ISO 3016
Flash point	> 240	°C	DIN EN ISO 2592

Application

TURMOFLUID 130 OM is used successfully in open gears, toothed gears and chains. It is especially applicable for wire ropes, guide ways, sliding points and switching cams.

Packaging units

6 x 5 l canisters, 20 l canister, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>