



TURMOFLUID 150 HF



Date of issue: 30.06.2020

TURMOFLUID 150 HF is a special chain oil lubricant based on synthetic oil with stabile oxidation inhibits and special EP-additives.

Special properties

- Excellent adhesion
- Very good wear protection
- Very good high load carrying capacity
- High oxidation resistance
- High temperature stability

Product Characteristics	Value	Dimension	Norm / Standard
Colour	brownish / transparent		
Density at 20°C	0,98	g/cm ³	DIN 51757
Operating temperature range	-20 to 280	°C	
Oil type	Ester		
Kinematic viscosity at 40°C	150	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	17,0	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	122		DIN ISO 2909
Pour point	< -30	°C	DIN ISO 3016
Flash point	≥ 280	°C	DIN EN ISO 2592

Application

For oil lubricated chains of thermal high loads in drying installations, varnishing plants, stenter frames. Wood-industry: Conti-roller plants, bared-shaped roller chains and steel belt lubrication.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>