



TURMOFLUID 20 B MF



Date of issue: 17.08.2017

TURMOFLUID 20 B MF is a thermally stable and extremely adherent synthetic chain oil with solid lubricants.

TURMOFLUID 20 B MF forms a wear protecting lubrication film.

Special properties

- Very good viscosity-temperature behaviour
- High oxidation resistance
- Excellent corrosion and wear protection
- High ageing resistance
- Low volatility
- Excellent adhesion

Product Characteristics	Value	Dimension	Norm / Standard
Colour	anthracite		
Density at 20°C	0,98	g/cm ³	DIN 51757
Operating temperature range	-25 to 225	°C	
Operating temperature range short time	up to 250	°C	
Oil type	Ester		
Kinematic viscosity at 40°C	103	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	14	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	138		DIN ISO 2909
Pour point	< -35	°C	DIN ISO 3016

Application

TURMOFLUID 20 B MF can be used for chains in heated equipment and for conveyor chains in the wood industry, in driers, steamers, chains of film stretching machines.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>