



TURMOFLUID 3 OM



Date of issue: 02.03.2021

TURMOFLUID 3 OM is a fully synthetic adhesive lubricating oil.

Special properties

- Excellent adhesion
- Excellent corrosion and wear protection
- High oxidation resistance
- Reduces friction and wear
- High load carrying capacity
- Easy cleaning of the machine parts because there is no hard incrustation

Product Characteristics	Value	Dimension	Norm / Standard
Colour	green-transparent		
Density at 20°C	0,91	g/cm ³	DIN 51757
Operating temperature range	-35 to 160	°C	
Oil type	Ester		
Kinematic viscosity at 40°C	27	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	7,5	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	268		DIN ISO 2909
Pour point	-47	°C	DIN EN ISO 3016
Flash point	> 190	°C	DIN EN ISO 2592

Application

TURMOFLUID 3 OM is used successfully in chains, guideways and diverse other sliding points.

TURMOFLUID 3 OM is especially applicable for bearer rings in the printing industry.

Packaging units

6 x 1 l bottles, 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>