



TURMOFLUID 4800 MF



Date of issue: 23.04.2015

TURMOFLUID 4800 MF is a tacky high temperature oil. It is a composition of high-boiling mineral oils, polymers, additives and solid lubricants.

Special properties

- High load carrying capacity
- Excellent corrosion protection
- Excellent nonferrous metal protection and aging protection
- Neutral to sleeves and sealing material

Product Characteristics	Value	Dimension	Norm / Standard
Colour	anthracite		
Density at 20°C	0,904	g/cm ³	DIN 51757
Operating temperature range	-5 to 130	°C	
Oil type	mineral oil		
Kinematic viscosity at 40°C	4800	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 50°C	2600	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	208	mm ² /s	DIN EN ISO 3104
Flash point	> 250	°C	DIN EN ISO 2592

Application

Well approved for longtime and permanent lubrication at highly stressed high-speed timing chains. Also suitable for closed tooth gear drives and worm gears, as well as for slideways and sliding components.

Packaging units

6 x 1 l bottles, 6 x 5 l canisters, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>