



TURMOFLUID 60 B



Date of issue: 13.03.2014

TURMOFLUID 60 B is a thermally stable and extremely adherent synthetically chain oil. It shows excellent penetration due to its low surface tension.

TURMOFLUID 60 B forms a transparent, extremely adherent lubricating film.

Special properties

- Excellent adhesion
- Low volatility
- Excellent corrosion and wear protection
- High oxidation resistance
- Very good viscosity-temperature behaviour
- Completely miscible with mineral oil
- Resistant to hot water
- Silicone-free

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellow, transparent		
Density at 20 °C	0,980	g/cm ³	DIN 51757
Operating temperature range	-10 to 260	°C	
Oil type	ester		
Kinematic viscosity at 40 °C	618	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100 °C	59,7	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	165		DIN ISO 2909
Pour point	< -30	°C	DIN ISO 3016
Flash point	> 180	°C	DIN EN ISO 2592

Application

TURMOFLUID 60 B can be used for all types of chains in heated equipment up to 260 °C, for all types of conveyor chains e.g. in the wood industry, in driers, steamers, chains of film stretching machines etc.

Application

TURMOFLUID 60 B may be applied manually, by drip-feed lubricators and by central lubrication systems.

Packaging units

6 x 1 l bottles, 6 x 5 l canisters, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>