



TURMOFLUID 60 BS



Date of issue: 28.08.2018

TURMOFLUID 60 BS is a synthetic, thermally stable and high temperature chain oil.

TURMOFLUID 60 BS forms an extremely adherent, wear-protecting lubricating film.

Special properties

- Low volatility
- Low moment of friction
- Low power consumption
- Free of polluting heavy metals
- High resistance to temperature
- High load carrying capacity

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellowish, transparent		
Density at 20°C	0,97	g/cm ³	DIN 51757
Operating temperature range	to 260	°C	
Oil type	Ester		
Kinematic viscosity at 40°C	820	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	77	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	158		DIN ISO 2909
Pour point	-10	°C	DIN ISO 3016
Flash point	230	°C	DIN EN ISO 2592

Application

Suitable for oil lubricated chains under high thermally load in drying and varnishing plants as well as stenter frames in the textile industry.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>