



## TURMOFLUID DAB 17



Date of issue: 10.10.2017

**TURMOFLUID DAB 17** is a multipurpose oil, based on high-purity hydrocarbons. In the food processing industry the oil can be used as physiologically safe lubricating and hydraulic oil.

### Special properties

- For the food industry, physiologically safe
- Odourless and tasteless
- High oxidation stability (no resinification, not pasting together)
- Very good lubricity
- Silicone-free

Product Characteristics	Value	Dimension	Norm / Standard
Colour	colourless, clear		
Density at 20°C	0,85	g/cm <sup>3</sup>	DIN 51757
Operating temperature range	-10 to 120	°C	
Oil type	White oil		
Kinematic viscosity at 40°C	16,5	mm <sup>2</sup> /s	DIN EN ISO 3104
Pour point	-12	°C	DIN ISO 3016
Flash point	> 180	°C	DIN EN ISO 2592

### Application

Lubricating and friction points in the food, beverage, cosmetic and pharmaceutical industry, where physiologically safe lubricants have to be applied.

### Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)  
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>