



## TURMOFLUID FTO



Date of issue: 25.09.2014

**TURMOFLUID FTO** is a chain lubricant based on mineral oil.

### Special properties

- Very good wear protection
- Very good corrosion protection
- Excellent load capacity of the lubricating film

Product Characteristics	Value	Dimension	Norm / Standard
Colour	brownish		
Density at 20°C	0,841	g/cm <sup>3</sup>	DIN 51757
Operating temperature range	-20 to 120	°C	
Oil type	mineral oil		
Kinematic viscosity at 40°C	134	mm <sup>2</sup> /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	16,1	mm <sup>2</sup> /s	DIN EN ISO 3104
Viscosity index (VI)	127		DIN ISO 2909
Pour point	≤ -20	°C	DIN ISO 3016
Flash point	≥ 200	°C	DIN EN ISO 2592

### Application

**TURMOFLUID FTO** is used for the lubrication of chains in escalators.

### Packaging units

6 x 1 l bottle, 5 l canister, 20 l canister

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)  
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>