



## TURMOFLUID GV 4000 TB 75



Date of issue: 09.08.2018

**TURMOFLUID GV 4000 TB 75** is a semi-synthetic lubricant based on highly refined mineral oils with polymer additives as well as additives, which are corrosion and wear protecting. After evaporation of the solvent, it creates an excellent adhesive, thin lubricating film.

### Special properties

- Very good wear protection
- Very good corrosion protection
- Good adhesive properties
- Well suited for slide friction

Product Characteristics	Value	Dimension	Norm / Standard
Colour	brownish / transparent		
Density at 20°C	1,18	g/cm <sup>3</sup>	DIN 51757
Operating temperature range	-15 to 120	°C	
Oil type	Mineral oil		
Kinematic viscosity at 40°C	40	mm <sup>2</sup> /s	DIN EN ISO 3104

### Application

Closed toothed gears and worm gears, high speed and high pressure loaded drive chains and steering chains, wires, friction points with high sliding portions, especially under influence of water or aggressive media as alkalis and acids.

### Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>