



TURMOFLUID HEM 12



Date of issue: 05.09.2018

TURMOFLUID HEM 12 is a clear and specially tight cut metal processing oil with excellent cooling capacities. Higher concentrations on additives allow a longer endurance of tools.

Special properties

- High lubrication quality
- Good heat dissipation from the contact points
- Residue-free evaporation
- No agglutination of packed stamped parts
- No disorder at welding operations
- High tool life

Product Characteristics	Value	Dimension	Norm / Standard
Colour	colourless, clear		
Density at 20°C	0,77	g/cm ³	DIN 51757
Oil type	Hydrocarbon mixture		
Kinematic viscosity at 20°C	1,1	mm ² /s	DIN EN ISO 3104
Pour point	≤ -20	°C	DIN ISO 3016
Flash point	36	°C	DIN EN ISO 2592

Application

Operations in punching and forming.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>