



TURMOFLUID MB DL 36



Date of issue: 12.05.2015

TURMOFLUID MB DL 36 is a special oil for pneumatic lines.

Special properties

- High ageing stability
- Excellent corrosion protection
- Very good wear protection
- Absorbs condensation
- Free of silicone, resin and acid

Product Characteristics	Value	Dimension	Norm / Standard
Colour	amber coloured, transparent		
Density at 20°C	0,87	g/cm ³	DIN 51757
Oil type	mineral oil		
Kinematic viscosity at 40°C	32	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	5,4	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	102		DIN ISO 2909
Pour point	< -20	°C	DIN ISO 3016
Flash point	> 200	°C	DIN EN ISO 2592

Application

Pneumatically driven machines, tools as well as pneumatical cylinders and pneumatical controls.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>