



TURMOFLUID MB SOK



Date of issue: 07.05.2015

TURMOFLUID MB-SOK is a high performance grinding oil for hard metal.

Special properties

- Chlorine- and zinc-free
- No tendency to smoke formation
- Almost odourless

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellow, transparent		
Density at 20°C	0,84	g/cm ³	DIN 51757
Oil type	mineral oil		
Kinematic viscosity at 40°C	3 - 4	mm ² /s	DIN EN ISO 3104
Pour point	approx. -18	°C	DIN ISO 3016
Flash point	> 120	°C	DIN EN ISO 2592
Refractive index	1,4610		DIN 51423

Application

Hard metal grinding at high operational speed. **TURMOFLUID MB SOK** has a limited suitability for use with non-ferrous metals. There is a risk of discolouration.

TURMOFLUID MB SOK is used undiluted.

Packaging units

6 x 5 l canisters, 20 l canister, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>