



TURMOFLUID MB ST 2 EP



Date of issue: 25.08.2015

Punch and drawing oil. Pure mixture of hydrocarbons with additives. These additives give a high load carrying capability and a high lubricating properties to the oil.

Special properties

- Free of fluorinated hydrocarbons
- Residue-free evaporation
- High lubrication quality
- No agglutination of packed stamped parts
- No disorder at welding operations
- Excellent wear protection because of newest additive technology
- High tool life

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellowish		
Density at 20°C	0,75	g/cm ³	DIN 51757
Oil type	Hydrocarbon mixture		
Kinematic viscosity at 40°C	1,6	mm ² /s	DIN EN ISO 3104
Pour point	< -15	°C	DIN ISO 3016
Flash point	> 57	°C	DIN EN ISO 2592

Application

Non-cutting metal working, especially suitable for punching and wire drawing processes.

Packaging units

1 l bottle, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>