



TURMOFLUID RD 2007-044-16 oil



Date of issue: 13.11.2013

TURMOFLUID RD 2007-044-16 oil is a synthetic high-temperature chain oil. It is especially used for the chain lubrication in conveyor plants as well as lacquer driers because of its overpaintability.

Special properties

- Overpaintable
- Minimal crater formation at direct contamination
- Silicon-free
- Free of MoS₂
- Very good wear protection
- Can be applied by automatic lubricators

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellow		
Density at 20 °C	1,04	g/cm ³	DIN 51757
Operating temperature range	-30 to 220	°C	
Oil type	polyglycol		
Kinematic viscosity at 40 °C	79	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100 °C	15	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	202		DIN ISO 2909
Pour point	-40	°C	DIN ISO 3016
Flash point	> 220	°C	DIN EN ISO 2592

Application

Lubrication of high temperature loaded chains of conveyor plants, lacquer driers etc..

Packaging units

6 x 1 l bottles, 6 x 5 l canister, 20 l canister, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>