



TURMOFLUID UEL 120



Date of issue: 23.08.2018

TURMOFLUID UEL 120 is a synthetic high-temperature oil.

TURMOFLUID UEL 120 is completely paintable and therefore recommended specially for the lubricating of chains in varnishing machines.

Special properties

- High chemical resistance
- High oxidation resistance
- Excellent corrosion and wear protection
- Very good adhesion
- Very good viscosity-temperature behaviour
- Long life at high temperatures
- Free of polluting heavy metals
- Silicone-free

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellowish, transparent		
Density at 20°C	0,97	g/cm ³	DIN 51757
Operating temperature range	-20 to 250	°C	
Operating temperature range short time	270	°C	
Oil type	Ester		
Kinematic viscosity at 40°C	125	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	16,2	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	138		DIN ISO 2909
Pour point	-25	°C	DIN ISO 3016
Flash point	200	°C	DIN EN ISO 2592

Application

TURMOFLUID UEL 120 is a synthetic high-temperature oil.

TURMOFLUID UEL 120 is completely paintable and therefore recommended specially for the lubricating of chains in varnishing machines.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>