



TURMOFLUID VDL 150



Date of issue: 29.10.2018

TURMOFLUID VDL 150 is a compressor oil based on mineral oil according DIN 51506.

Special properties

- High oxidation resistance
- Good lubricating properties
- High resistance to temperature
- Very good corrosion protection
- Very good wear protection
- Reduction of residue formation

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellow, clear		
Density at 20°C	0,89	g/cm ³	DIN 51757
Oil type	Mineral oil		
Kinematic viscosity at 40°C	150	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	14,8	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	97		DIN ISO 2909
Pour point	-9	°C	DIN ISO 3016
Flash point	> 260	°C	DIN EN ISO 2592

Application

TURMOFLUID VDL 150 is used for the lubrication of stationary and mobile air compressors with oil lubricated pressure chambers.

TURMOFLUID VDL 150 is used for a max. final compression temperature of 220°C.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>