



TURMOFLUID VP 550



Date of issue: 15.10.2015

TURMOFLUID VP 550 is a specially designed lubricant for hoisting and conveyor chains, with very good adhesiveness and optimum wear protection.

Special properties

- High load carrying capacity
- Very good wear protection
- Excellent corrosion protection
- Good adhesive properties
- High oxidation stability (no resinification, not pasting together)

Product Characteristics	Value	Dimension	Norm / Standard
Colour	dunkelbraun / klar		
Density at 20°C	0,92	g/cm ³	DIN 51757
Operating temperature range	-10 to 150	°C	
Oil type	mineral oil		
Kinematic viscosity at 40°C	590	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	37	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	98		DIN ISO 2909
Pour point	-15	°C	DIN ISO 3016
Flash point	> 260	°C	DIN EN ISO 2592

Application

TURMOFLUID VP 550 is used for the lubrication of hoisting chains (e.g. forklifts). **TURMOFLUID VP 550** is furthermore used as adhesive lubricant in gears with limited thermal stress and on gliding surfaces. Special additives confer **TURMOFLUID VP 550** it's long fibrous properties.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>