

We have the solution...

...the future has a name



Technical Information

LUBRICANT CONSULT GMBH

Gutenbergstraße 13 · D-63477 Maintal – Germany · Telefon: +49-61 09 - 76 50-0 · Fax: +49-61 09 - 76 50-51 · Internet: www.lubcon.com

TURMOGEAR HSS

LUBCON - Adhesive Lubricant

TURMOGEAR HSS is a lubricant based on synthetic oil for open gears.

TURMOGEAR HSS reduces wear and noise and offers standing-out properties of adhesiveness and an excellent protection against corrosion.

TURMOGEAR HSS is dissolved in a light volatile and non-combustible solvent for an easier application and handling.

TURMOGEAR HSS has a very high pressure capacity which remains elastic under low temperatures and does not form any solid residues.

TURMOGEAR HSS is the ideal lubricant for the lubrication of large open gears and sliding points.

Technical Data

TURMOGEAR HSS

Colour	brownish/transparent
Base oil	SHC / Mineral oil
Density at 20°C	0,91 g/cm ³
Viscosity at 40°C DIN 51562	approx. 16000 mm ² /s
Pourpoint °C DIN ISO 3016	- 7
Flash Point °C DIN ISO 2592	> 200

Original Packing Units:

6 x 5 l cans, 20 ltr. cans

The products are subject to severe controls of manufacture and comply in full with the specifications set forth by our company. Due to the multitude of different influencing factors, we cannot assume any warranty for the successful in each case. Therefore, we recommend to perform field tests. We strictly refuse any liability.