

We have the solution...

...the future has a name



Technical Information

LUBRICANT CONSULT GMBH

Gutenbergstraße 13 · D-63477 Maintal – Germany · Telefon: +49-61 09 - 76 50-0 · Fax: +49-61 09 - 76 50-51 · Internet: www.lubcon.com

TURMOGEARGREASE N 00 Y **GP 00 R -40**

Issued: 16.09.2004

LUBCON-Synthetic High Temperature Gear Flow Grease

TURMOGEARGREASE N 00 Y is a soft and smooth special-grease for various applications at a temperature range of -40°C up to $+180^{\circ}\text{C}$.

Quality features

- cold and hot water resistant
- high pressure stability, i.e. load carrying properties
- excellent wear protection
- miscible with all lubricants on mineral oil base with soap or organic thickener
- optimum corrosion protection
- very good heat dissipation

TECHNICAL DATA

TURMOGEARGREASE N 00 Y

Colour	yellowish, beige
Temperature range	-40°C to $+180^{\circ}\text{C}$
Base oil	SHC
Thickener	Polyurea
Dropping point DIN ISO 2176	$> 200^{\circ}\text{C}$
Worked penetration DIN 2137	400 - 430
Consistency class DIN 51818	00
Corrosion protection (Emcor) DIN 51802	0 - 0

USES

In gears of electric tools, machine tools, actuating drives, needle bearings and for all applications where structurally viscous lubricants have to stop leakages and to reduce wear.

CONTAINER SIZES

6 x 1 kg-can, 25 kg hobbock, 180 kg drum