

# TURMOGAROIL TEX-WKA 680

## LUBCON – Synthetic Adhesive Oil

**TURMOGAROIL TEX-WKA 680** is a synthetic, long-fibrous special oil with a very good surface adhesion. Very new additive technology offers an optimum protection against wear specially in the lubrication of pivot bearings on annular spinning machines.

### QUALITY FEATURES

- good load performance
- good adhesive capacity
- high thermal resistance
- good wear properties
- good protection against corrosion

### TECHNICAL DATA

### TURMOGAROIL TEX-WKA 680

Colour / Appearance	yellowish,clear
Temperature range	-10°C up to +150°C
Density at +20°C	0,85 g/cm <sup>3</sup>
Viscosity at +40°C at +100°C	680 mm <sup>2</sup> /s 83 mm <sup>2</sup> /s
Viscosity index	204
Index of refraction n <sub>D</sub> <sup>20</sup>	1,4727
Flashpoint	>220°C
Pourpoint	-15°C

### Application:

**TURMOGAROIL TEX-WKA 680** is used for the lubrication of high-loaded slide areas.

**TURMOGAROIL TEX-WKA 680** is furthermore used as an adhesive lubricating oil in loaded gears and lift chains. The necessary tackiness of the lubricating oil is obtained due to the addition of special additives.

### Original Packing Units:

6/5 l cans, 20 l cans, 200 l drum (not returnable)