



TURMOGREASE Highspeed L 250

G P HC 0 K -40



Date of issue: 20.01.2016

TURMOGREASE HIGHSPEED L 250 is a special grease for spiral/helical-gearing with optimal surface adhesion.

Special properties

- Low heating in high speed gearboxes
- Low starting resistance and low frictional torque
- Very good low temperature properties
- Excellent anti-corrosion and anti-wear properties
- High metal affinity
- Suitable for long working life lubrication

Product Characteristics	Value	Dimension	Norm / Standard
Colour	beige		
Density at 20°C	0,90	g/cm ³	DIN 51757
Operating temperature range	-40 to 120	°C	
Thickener	Lithium special soap		
Base oil	SHC / Ester		
Kin. viscosity of the base oil at 40°C	25	mm ² /s	DIN EN ISO 3104
Kin. viscosity of the base oil at 100°C	6	mm ² /s	DIN EN ISO 3104
Worked penetration	355 – 385	mm/10	DIN ISO 2137
Consistency class (NLGI)	0		DIN 51818
Dropping point	> 180	°C	DIN ISO 2176
Resistance to water	1 – 90		DIN 51807
Corrosion protection (SKF-Emcor)	0 / 0		DIN 51802

Application

TURMOGREASE Highspeed L 250 is mainly used in gearboxes and spiral/helical-gearings with grease reservoir.

Packaging units

20 x 400 g cartridges, 6 x 1 kg cans, 5 kg bucket, 25 kg hobbock, 180 kg drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>