



# TURMOGREASE Highspeed L 252/00

G P HC 00 E -40



Date of issue: 21.09.2015

**TURMOGREASE Highspeed L 252/00** is a geargrease based on a lithium special soap. Particular additives optimize this lubricating grease.

### Special properties

- Excellent smooth running properties
- Excellent corrosion protection
- Very good wear protection
- High metal affinity

Product Characteristics	Value	Dimension	Norm / Standard
Colour	beige		
Operating temperature range	-40 to 80	°C	
Thickener	Lithium special soap		
Base oil	SHC / Ester		
Kin. viscosity of the base oil at 40°C	25	mm <sup>2</sup> /s	DIN EN ISO 3104
Kin. viscosity of the base oil at 100°C	6	mm <sup>2</sup> /s	DIN EN ISO 3104
Worked penetration	400 – 430	mm/10	DIN ISO 2137
Consistency class (NLGI)	00		DIN 51818
Corrosion protection ( SKF-Emcors)	0 / 0		DIN 51802

### Application

Gears in machine tools.

### Packaging units

20 x 400 g cartridges, 6 x 1 kg cans, 5 kg bucket, 25 kg hobbock, 180 kg drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>