



TURMOGREASE NBC 300 weiss

K P F HC 1/2 G -55



Date of issue: 09.06.2015

TURMOGREASE NBC 300 weiss is a lubricating, sealing and assembly paste with solid lubricants.

Special properties

- Very good low temperature properties
- Excellent water resistance
- Very good adhesion
- Very good corrosion protection
- Good sealing effect
- Neutral towards plastics

Product Characteristics	Value	Dimension	Norm / Standard
Colour	light beige		
Density at 20°C	0,97	g/cm ³	DIN 51757
Operating temperature range	-55 to 100	°C	
Thickener	Calcium soap		
Base oil	Synthetic hydrocarbons		
Kin. viscosity of the base oil at 40°C	82	mm ² /s	DIN EN ISO 3104
Kin. viscosity of the base oil at 100°C	13,2	mm ² /s	DIN EN ISO 3104
Worked penetration	290 -310	mm/10	DIN ISO 2137
Consistency class (NLGI)	1 – 2		DIN 51818
Dropping point	> 100	°C	DIN ISO 2176
Resistance to water	0 – 90		DIN 51807
Corrosion protection (SKF-Emcor)	0 / 0		DIN 51802
Flow pressure at -40°C	< 440	mbar	DIN 51805

Application

Lubrication of sliding and rolling bearings, for sealing and mounting purposes, especially in cases where tribo- and fretting corrosion should be avoided.

Packaging units

25 x 100 g tubes, 20 x 400 g cartridges, 6 x 0,5 kg cans, 6 x 1 kg cans, 5 kg bucket, 25 kg hobbock, 180 kg drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>