



## TURMOGREASE NBI 2 KPL

M P F 2 N -30



Date of issue: 07.05.2018

**TURMOGREASE NBI 2 KPL** is a water resistant, electrically conductive complex soap grease based on selected mineral oils.

### Special properties

- Optimum corrosion protection
- Very good wear protection
- Resistant to cold/hot water
- Resistant to weak acidic/ alkaline media
- Very good adhesive properties
- Electrically conductive

Product Characteristics	Value	Dimension	Norm / Standard
Colour	anthracite		
Density at 20°C	0,91	g/cm <sup>3</sup>	DIN 51757
Operating temperature range	-30 to 150	°C	
Thickener	Calcium complex soap		
Base oil	Mineral oil		
Kin. viscosity of the base oil at 40°C	100	mm <sup>2</sup> /s	DIN EN ISO 3104
Kin. viscosity of the base oil at 100°C	11,8	mm <sup>2</sup> /s	DIN EN ISO 3104
Worked penetration	265 – 295	mm/10	DIN ISO 2137
Consistency class (NLGI)	2		DIN 51818
Dropping point	> 250	°C	DIN ISO 2176
Resistance to water	0 – 90		DIN 51807
Corrosion protection ( SKF-Emcor)	0 / 0		DIN 51802

### Application

Corrosion protection for electrically conductive parts, like battery terminals.

### Packaging units

6 x 1 kg cans, 10 kg can

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>