



## TURMOGREASE RAH



Date of issue: 25.09.2018

**TURMOGREASE RAH** is a drawing, cutting and lubricating agent for materials difficult to machine and non-cutting shaping.

### Special properties

- Extended tool life
- Reduced tool fracture
- Machining time is reduced
- Improved quality of the surface

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellow		
Density at 20°C	0,96	g/cm <sup>3</sup>	DIN 51757
Operating temperature range	-10 to 100	°C	
Thickener	Aluminium soap		
Base oil	Ester		
Kin. viscosity of the base oil at 40°C	1000	mm <sup>2</sup> /s	DIN EN ISO 3104
Worked penetration	355 – 385	mm/10	DIN ISO 2137
Consistency class (NLGI)	0		DIN 51818
Dropping point	130	°C	DIN ISO 2176
Pour point	-20	°C	DIN ISO 3016

### Application

Drilling, turning, milling, thread-cutting, broaching, fretting, pushing and drawing.

### Packaging units

25 x 100 g tubes, 12 x 0,5 kg cans, 6 x 5 kg cans



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>