

We have the solution...

...the future has a name



## Technical Information

## LUBRICANT CONSULT GMBH

Gutenbergstraße 13 · D-63477 Maintal – Germany · Telefon: +49-61 09 - 76 50-0 · Fax: +49-61 09 - 76 50-51 · Internet: [www.lubcon.com](http://www.lubcon.com)

### TURMOLYB SUSPENSION 20 W

#### LUBCON – High Temperature-Chain Lubricant

##### Description

Aqueous suspension made of synthetic oil with a special solid lubricant combination. Preferential application at high temperatures up to +450 °C. A special production procedure prevents sedimentation of the solid lubricants.

##### Advantages

- smokeless, practically inodorous
- very good fretting reduction
- high load-carrying capacity
- good cushioning effect of vibrating
- slight formation of residues
- offers optimum corrosion protection
- high flash point of the active substance
- no irritant action on eyes or skin

##### Technical Data

##### TURMOLYB SUSPENSION 20 W

Colour	black
Solid content weight %	approx. 18
Density +20 °C (g/cm <sup>3</sup> )	approx. 1.1
Temperature range (°C)	+5 up to 450
Flashpoint (°C) - Base oil	> 230
Pourpoint (°C)	0

##### Application

Due to a residue-free decomposition of the base-oil, **TURMOLYB SUSPENSION 20 W** is specially qualified for the application of chain-lubrication in annealing installations, furnaces and drying kilns under thermal stress.

##### Application Method

By means of spray gun or by immersion.

##### Original Packaging

6 x 1 kg can, 5 kg resp. 20 kg can, 60 kg drum (not returnable)