



TURMOLYB Suspension LMI



Date of issue: 29.04.2019

TURMOLYB Suspension LMI is an aqueous suspension of a special solid combination. Preferred applicable at high temperatures of up to 500°C. A special additivation avoids the separation of the solid lubricants.

TURMOLYB Suspension LMI is InS H1 registered as lubricant for which an incidental contact with food technically cannot be avoided.

Special properties

- Good reduction of friction coefficient
- High load carrying capacity
- Nearly no addition to sedimentation
- Builds up a dry, well adhesive sliding film
- Offers excellent corrosion protection
- Non-combustible
- Not harmful to the environment and user-optimized

Product Characteristics	Value	Dimension	Norm / Standard
Colour	milky white		
Density at 20°C	1,02	g/cm ³	DIN 51757
Operating temperature range	-70 to 500	°C	
Flash point	not inflammable	°C	DIN EN ISO 2592
pH value	10-12		

Application

TURMOLYB Suspension LMI is particularly suitable as a lubricant and release agent in the food industry.

Applicable through brush, spray pistol or dipping bath.

Product has to be shaken or stirred before usage.

Protect from frost.

Packaging units

1 l bottle, 5 l canister, 20 l canister, 60 l drum



1795811



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>