

We have the solution...

...the future has a name



Technical Information

LUBRICANT CONSULT GMBH

Gutenbergstraße 13 · D-63477 Maintal – Germany · Telefon: +49-61 09 - 76 50-0 · Fax: +49-61 09 - 76 50-51 · Internet: www.lubcon.com

TURMOLYB WG SUSPENSION EP

LUBCON High temperature sliding and separating agent

Product Description

White, solid lubricant suspension with excellent adhesive properties on metallic, mineral and glass type surfaces. The dry lubricating film has excellent separating and protecting properties against corrosion and wear.

Advantages

- excellent surface adhesion
- minimum friction value
- very good pressure absorption capacity
- no irritant action towards eyes and skin
- toxic safely, no dangerous decomposition products

Technical Data

TURMOLYB WG SUSPENSION EP

Colour	whitish
Solid content	approx. 12 %
Density	approx. 1.03g/cm ³ at +20 °C
Operating temperature	up to approx. +1200 °C

Application

TURMOLYB TG is successfully used as separating agent in the plastic industry, metal extruding, as well as lubrication of bed and sliding tracks in the machine building industry.

Handling

By means of coating pistol, brush, paint roll or dipping bath the suspension should be thinly distributed to the grease and oil free surface, wait for complete drying.

Original Packaging

5 l cans, 20 l can