



TURMOPAST TAS WT 000 CRY

G P F 000 R -20



Date of issue: 16.05.2019

TURMOPAST TAS WT 000 CRY is a sprayable adhesive gear grease containing graphite. It does not drip off at high temperatures and does not sling off at high peripheral speed.

Special properties

- Very good adhesive properties
- Excellent corrosion protection
- Very good wear protection
- Very high load carrying capacity
- High lubricating film stability
- High metal affinity
- Very good sprayable

Product Characteristics	Value	Dimension	Norm / Standard
Colour	anthracite		
Density at 20°C	0,93	g/cm ³	DIN 51757
Operating temperature range	-20 to 180	°C	
Thickener	Aluminium complex soap		
Base oil	Mineral oil		
Kin. viscosity of the base oil at 40°C	500	mm ² /s	DIN EN ISO 3104
Unworked penetration	480 - 500	mm/10	DIN ISO 2137
Consistency class (NLGI)	approx. 000		DIN 51818
Resistance to water	0 – 90		DIN 51807
Corrosion protection (SKF-Emcor)	0 / 0		DIN 51802
FZG-test A/2,76/50	> 12		DIN 51354
Four-ball welded load	> 5000	N	DIN 51350

Application

For all closed toothed drives, joints and steel cables.

Packaging units

6 x 1 kg can, 5 kg bucket, 25 kg hobbock



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>