



## TURMOPLEX extraleicht FN

G P 00 K -40



Date of issue: 06.08.2018

**TURMOPLEX extraleicht FN** is a lithium saponified semi-fluid grease for lubrication of gears and gear motors.

### Special properties

- High load carrying capacity
- Very good corrosion protection
- High oxidation resistance
- Good wear protection
- Conveyable in central-lubrication systems
- Usable in feeding lubricating systems

Product Characteristics	Value	Dimension	Norm / Standard
Colour	green		
Density at 20°C	0,90	g/cm <sup>3</sup>	DIN 51757
Operating temperature range	-40 to 120	°C	
Thickener	Lithium soap		
Base oil	Synth. HC / Mineral oil		
Kin. viscosity of the base oil at 40°C	45	mm <sup>2</sup> /s	DIN EN ISO 3104
Worked penetration	400 – 430	mm/10	DIN ISO 2137
Consistency class (NLGI)	00		DIN 51818
Dropping point	> 180	°C	DIN ISO 2176
Resistance to water	1 – 90		DIN 51807

### Application

Central lubrication systems for commercial vehicles.

### Packaging units

6 x 1 kg can, 5 kg bucket, 25 kg hobbock, 180 kg drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>