



# TURMOPLEX LC leicht NLGI 0

G P 0 K -30



Date of issue: 12.09.2017

**TURMOPLEX LC leicht NLGI 0** is a lithium/calcium saponified high performance semifluid grease.

### Special properties

- High load carrying capacity
- Very good wear protection
- Good corrosion protection
- High oxidation resistance
- Very good water resistance
- Good low temperature behaviour
- Conveyable in central-lubrication systems

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellowish brown		
Density at 20°C	0,89	g/cm <sup>3</sup>	DIN 51757
Operating temperature range	-30 to 120	°C	
Base oil	Mineral oil		
Kin. viscosity of the base oil at 40°C	120	mm <sup>2</sup> /s	DIN EN ISO 3104
Worked penetration	355 – 385	mm/10	DIN ISO 2137
Consistency class (NLGI)	0		DIN 51818
Dropping point	> 150	°C	DIN ISO 2176
Resistance to water	0 – 90		DIN 51807

### Application

Proved in gear units, gear motors, sliding rails and guideways.

### Packaging units

25 kg hobbock, 180 kg drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>