



TURMOTEMP M 182 Fluid 90-480



Date of issue: 11.10.2017

TURMOTEMP M 182 Fluid 90-480 is a prediluted dispersion of **TURMOTEMP M 182** in **TURMOTEMPOIL 480**.

Technical data of **TURMOTEMP M 182** available on a separate data sheet.

Product Characteristics	Value	Dimension	Norm / Standard
Colour	milky white		
Density at 20°C	1,7	g/cm ³	DIN 51757
Operating temperature range	to approx. 55	°C	
Thickener	PTFE		
Base oil	PFPE		
Kin. viscosity of the base oil at 40°C	18	mm ² /s	DIN EN ISO 3104
Kin. viscosity of the base oil at 100°C	5,2	mm ² /s	DIN EN ISO 3104

Application

TURMOTEMP M 182 Fluid 90-480 is used for preservation and thin-film lubrication of all bearing types and various seals.

Shake dispersion well before use.

Packaging units

1 l bottle, 5 l canister, 20 l canister

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>