



TURMOWOODOIL OSB



Date of issue: 17.08.2020

TURMOWOODOIL OSB is a fully synthetic high-performance oil.

Special properties

- Excellent wear protection
- Very good corrosion protection
- High resistance towards oxidation and high temperatures
- Low volatility
- Good compatibility with PMDI glue
- Silicone-free

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellow, clear		
Density at 20°C	0,98	g/cm ³	DIN 51757
Operating temperature range	-20 to 260	°C	
Oil type	Ester		
Copper corrosion 24 h/100°C	1a		DIN 51811
Kinematic viscosity at 40°C	230	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	20	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	100		DIN ISO 2909
Pour point	-25	°C	DIN ISO 3016
Flash point	> 270	°C	DIN EN ISO 2592

Application

High performance belt and chain oil for OSB presses.

Packaging units

20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>