



TURMSILON K 350 WR



Date of issue: 08.11.2018

TURMSILON K 350 WR is a heat stabilized silicone oil, based on polymethylsiloxanes.

Special properties

- Very good viscosity-temperature behaviour
- Excellent sealing compatibility
- High compressibility
- Low vapour pressure
- Wide temperature range
- Heat stabilised

Product Characteristics	Value	Dimension	Norm / Standard
Colour	amber coloured, transparent		
Density at 20°C	0,97	g/cm ³	DIN 51757
Operating temperature range	-50 to 250	°C	
Oil type	Silicone oil		
Kinematic viscosity at 25°C	350	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 40°C	290	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	125	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	450		DIN ISO 2909
Pour point	≤ -50	°C	DIN ISO 3016
Flash point	> 300	°C	DIN EN ISO 2592

Application

TURMSILON K 350 WR is used as thermal oil.

TURMSILON K 350 WR is suitable as lubricating oil for material pairing plastic / metal or plastic / plastic.

Packaging units

6 x 5 l canisters, 20 l canister, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>