



TURMSILON K 500 WF



Date of issue: 21.01.2016

TURMSILON K 500 WF is a heat stabilized silicone oil, based on polymethylsiloxanes.

Special properties

- Very good viscosity-temperature behaviour
- Excellent sealing compatibility
- High compressibility
- Low vapour pressure
- Wide temperature range
- Heat stabilised

Product Characteristics	Value	Dimension	Norm / Standard
Colour	red brown, clear		
Density at 20°C	0,97	g/cm ³	DIN 51757
Operating temperature range	-50 to 250	°C	
Oil type	silicone oil		
Kinematic viscosity at 25°C	500	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 40°C	410	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	163	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	440		DIN ISO 2909
Pour point	≤ -50	°C	DIN ISO 3016
Flash point	> 250	°C	DIN EN ISO 2592

Application

TURMSILON K 500 WF is used as thermal oil.

Packaging units

20 l canister, 200 l drum, 1000 l container

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>