



TURMSILON KE 35 EMULSION



Date of issue: 09.09.2019

TURMSILON KE 35 EMULSION is an easy-to-use silicone emulsion used as a release agent or lubricant.

Special properties

- Excellent release properties
- Very good sliding properties
- High resistance to temperature
- Good lubricating properties
- Water repellent lubricant film

Product Characteristics	Value	Dimension	Norm / Standard
Colour	milky white		
Density at 20°C	0,99	g/cm ³	DIN 51757
Oil type	Silicone oil / water		
Boiling point	approx. 100	°C	
Flash point	without	°C	DIN EN ISO 2592

Application

TURMSILON KE 35 EMULSION can be applied to surfaces as a release agent by spraying, dipping or painting.

TURMSILON KE 35 EMULSION is used as a lubricant for rubber stoppers and seals on screw heads or as a release agent in the manufacture of plastic pipes, polyethylene carrier bags and extruded rubber parts.

In the textile industry it is used as a lubricant for yarns and threads to prevent premature needle wear or breakage.

In addition, **TURMSILON KE 35 EMULSION** is a component for the production of automotive and furniture polishes and can also be used in diluted form as an all-purpose polish.

Note

TURMSILON KE 35 EMULSION can be diluted in any ratio with, preferably decalcified, water.

The optimum storage temperature is between 0°C and +30°C. If stored below 0°C for a longer period of time, the emulsifier may freeze, but is fully usable again after thawing.

Packaging units

1 l bottle, 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>